


POWER MODULES

IRK.105 SERIES High Voltage Diode/Diode

FEATURES

- ◆ *Electrically isolated base plate.*
- ◆ *3500 V_{RMS} isolating voltage.*
- ◆ *Simplified mechanical designs, rapid assembly.*
- ◆ *High surge capability.*
- ◆ *Large creepage distances.*
- ◆ *Aluminum Nitride*



DESCRIPTION

These IRK series of Power Modules use power diodes in three basic configurations. The semiconductors are electrically isolated from the metal base, allowing common heatsinks and compact assemblies to be built. They can be interconnected to form single phase or three phase bridges.

These modules are intended for general purpose applications such as battery chargers, welders and plating equipment.

MAJOR RATINGS & CHARACTERISTICS

Parameters		IRK.105	Units
$I_{T(AV)}$	$T_c = 87^\circ\text{C}$	105	A
$I_{T(RMS)}$		164	A
I_{TSM}	@ 50 Hz	2020	A
I^2t	@ 50 Hz	20430	A ² s
I^2t		204300	A ² s
V_{RRM}	range	400 to 1600	V
T_j	range	-40 to 135	°C

(*) Contact factory for higher voltages (1600-2000V) and higher currents (60, 80, 100 A)

POWER MODULES

IRK. 105 SERIES

ELECTRICAL SPECIFICATION VOLTAGE RATINGS

Type Number	Voltage Code	V_{RRM} max. repetitive peak reverse voltage V	V_{RSM} max. non-repetitive peak reverse voltage V	I_{RRM} max. @ $T_J = T_J \text{ max}$ mA
IRK.105	04	400	500	10
	06	600	700	10
	08	800	900	10
	10	1000	1100	10
	12	1200	1300	10
	14	1400	1500	10
	16	1600	1700	10

FORWARD CONDUCTION

	Parameters	IRK.105	Units	Conditions
$I_{F(AV)}$	Max. average forward current	105	A	180°C conduction, half sine wave
	@ case temperature	87	°C	
$I_{F(RMS)}$	Max. RMS forward current	164	A	
I_{FSM}	Max. peak, one cycle forward non-repetitive surge current	2020	A	t = 10ms
I^2t	Maximum I^2t for fusing	20430	A ² s	t = 10ms
I^2t	Maximum I^2t for fusing	204300	A ² s	t = 0.1 to 10ms.
$V_{F(TO)}$	Threshold Voltage	0.66	V	$T_J = T_J \text{ max.}$
r_t	forward slope resistance	1.81	mΩ	$T_J = T_J \text{ max.}$
V_{FM}	Max. forward voltage drop	1.34	V	$I_{FM} = \pi \times I_{F(AV)}$, $T_J = 25^\circ\text{C}$, $t_p = 400\mu\text{s}$ squarewave AV. power = $V_{F(TO)} \times I_{F(AV)} + r_1 \times (I_{F(RMS)})^2$

POWER MODULES

IRK. 105 SERIES

THERMAL AND MECHANICAL SPECIFICATIONS


	Parameter	IRK.105	Units	Conditions
T_J	Junction operating temperature	-40 to 135	°C	
T_{stg}	Storage temperature range	-40 to 150	°C	
R_{thJ-C}	Max. internal thermal resistance, junction to case	0.22	K/W	IRKD../IRKJ../IRKC.. Per module, DC operation
R_{thC-S}	Thermal resistance, case to heatsink	0.1	K/W	Mounting surface flat, smooth and greased
T	Mounting torque $\pm 10\%$ Module to heatsink	5	Nm	A mounting compound is recommended and the torque should be rechecked after a period of about 3 hours to allow for the spread of the compound.
	Busbar to module	3	Nm	
Wt	Approximate weight	115	g	

BLOCKING

	Parameters	IRK.105	Units	Conditions
I_{RRM}	Max. peak reverse leakage current	10	mA	$T_J = 135^\circ\text{C}$
V_{INS}	RMS isolation voltage	3500	V	50 Hz circuit to base, all terminals shorted, $t = 1\text{s}$

POWER MODULES

OUTLINE DRAWING



Ordering Information Table

Device Code			
IRK	D	105	/ 16
①	②	③	④
1	- Module type		
2	- Circuit configuration (See Circuit Configuration Table)		
3	- Current code		
4	- Voltage code (See Voltage Ratings Table)		

Circuit Configurations Table

